

Instrumentation & Communication Cable



Cable Designation (S108)

250V BU(c)

Application Standard

- Design guide : NEK-606 & IEC 60092-376
- Flame retardant : IEC 60332-1 & IEC 60332-3 Category A
- Fire resistance : IEC 60331-21(90min) IEC 60331-1,-2(120min)
- Halogen content : IEC 60754-1, 0.5%↓
- Cold bend / impact : CSA C22.2 No. 2556 or IEC 60092-350 Annex.E Method 1 (-40°C/-35°C)
- Mud / Oil resistant : NEK 606 (Category a,b,c,d)
- Smoke light transmittance : IEC 61034, 60%↑
- Sunlight (UV) resistant : UL 1581

Construction

Sectional view	Classification	Code	Construction detail
	Conductor		- Stranded tinned annealed copper wires as per IEC 60228, Class 2
	Fire resisting layer	B	- Mica/glass tape
	Insulation		- EPR as per IEC 60092-360
	Twisting		- Two/Three Insulated cores shall be twisted together to form a pair/Triad
	Cabling		- Twisted pairs / triads shall be cabled - Flame retardant & non-hygroscopic fillers may be used - Suitable tape(s) may be applied on the cabled core - A Filler may be applied to obtain a circular Cable
	Collective screen	(c)	- CU/PS or AL/PS tape + Tinned copper drain wire
	Sheath	U	- SHF2 as per IEC 60092-360 - Option : NEK 606 Category a,b,c,d Mud or oil resistant - Outer sheath color : Grey (Non-IS Type) or Blue (IS Type)
Core identification			- Each Pair / Triad : Core color ① Pair : Black, Light blue ② Triad : Black, Light blue, Brown - Multi Pairs / Triads : Number printing on the insulation or numbered tape

Note. Flexible cable (Class5 Conductor) can be supplied

250V BU(c)

No. of Pairs	Conductor			Thickness of Insulation	Thickness of sheath	Overall diameter		Conductor Resistance (at 20°C) (Max.)	Insulation Resistance (at 20°C) (Min.)	Test Voltage	Cable Weight Approx.
	Nominal Area	Max. No. of wires	Max. overall dia.			Nominal	Tolerance				
No.	mm ²	EA	mm	mm	mm	mm	±mm	Ω/km	MΩ·km	V/5min.	kg/km
1P	0.75	7	1.2	0.6	1.0	8.6	0.9	26.3	1,170	1,500	110
2P	0.75	7	1.2	0.6	1.2	13.0	1.0	26.3	1,170	1,500	220
3P	0.75	7	1.2	0.6	1.2	13.8	1.0	26.3	1,170	1,500	260
4P	0.75	7	1.2	0.6	1.3	14.9	1.1	26.3	1,170	1,500	310
5P	0.75	7	1.2	0.6	1.3	16.6	1.1	26.3	1,170	1,500	380
6P	0.75	7	1.2	0.6	1.4	18.0	1.1	26.3	1,170	1,500	450
7P	0.75	7	1.2	0.6	1.4	18.0	1.1	26.3	1,170	1,500	460
8P	0.75	7	1.2	0.6	1.4	19.2	1.2	26.3	1,170	1,500	520
10P	0.75	7	1.2	0.6	1.5	21.7	1.3	26.3	1,170	1,500	660
12P	0.75	7	1.2	0.6	1.6	22.8	1.3	26.3	1,170	1,500	740
14P	0.75	7	1.2	0.6	1.6	23.6	1.3	26.3	1,170	1,500	810
16P	0.75	7	1.2	0.6	1.7	25.6	1.4	26.3	1,170	1,500	950
19P	0.75	7	1.2	0.6	1.7	26.7	1.4	26.3	1,170	1,500	1,050
24P	0.75	7	1.2	0.6	1.9	30.6	1.5	26.3	1,170	1,500	1,370
32P	0.75	7	1.2	0.6	2.0	34.9	1.7	26.3	1,170	1,500	1,780
1P	1.0	7	1.4	0.6	1.1	9.2	0.9	19.3	1,050	1,500	130
2P	1.0	7	1.4	0.6	1.2	13.6	1.0	19.3	1,050	1,500	250
3P	1.0	7	1.4	0.6	1.3	14.8	1.1	19.3	1,050	1,500	310
4P	1.0	7	1.4	0.6	1.3	15.7	1.1	19.3	1,050	1,500	350
5P	1.0	7	1.4	0.6	1.4	17.8	1.1	19.3	1,050	1,500	450
6P	1.0	7	1.4	0.6	1.4	19.0	1.2	19.3	1,050	1,500	510
7P	1.0	7	1.4	0.6	1.4	19.0	1.2	19.3	1,050	1,500	530
8P	1.0	7	1.4	0.6	1.5	20.4	1.2	19.3	1,050	1,500	610
10P	1.0	7	1.4	0.6	1.6	23.1	1.3	19.3	1,050	1,500	770
12P	1.0	7	1.4	0.6	1.6	24.1	1.3	19.3	1,050	1,500	850
14P	1.0	7	1.4	0.6	1.7	25.2	1.4	19.3	1,050	1,500	960
16P	1.0	7	1.4	0.6	1.7	27.0	1.4	19.3	1,050	1,500	1,090
19P	1.0	7	1.4	0.6	1.8	28.5	1.5	19.3	1,050	1,500	1,240
24P	1.0	7	1.4	0.6	1.9	32.4	1.6	19.3	1,050	1,500	1,580
32P	1.0	7	1.4	0.6	2.1	37.1	1.7	19.3	1,050	1,500	2,090
1P	1.5	7	1.7	0.7	1.1	10.1	1.0	12.9	1,020	1,500	160
2P	1.5	7	1.7	0.7	1.3	15.5	1.2	12.9	1,020	1,500	320
3P	1.5	7	1.7	0.7	1.3	16.5	1.2	12.9	1,020	1,500	380
4P	1.5	7	1.7	0.7	1.4	17.8	1.2	12.9	1,020	1,500	460
5P	1.5	7	1.7	0.7	1.5	20.2	1.4	12.9	1,020	1,500	580
6P	1.5	7	1.7	0.7	1.5	21.6	1.4	12.9	1,020	1,500	660
7P	1.5	7	1.7	0.7	1.5	21.6	1.4	12.9	1,020	1,500	700
8P	1.5	7	1.7	0.7	1.6	23.2	1.4	12.9	1,020	1,500	800
10P	1.5	7	1.7	0.7	1.7	26.3	1.6	12.9	1,020	1,500	1,010
12P	1.5	7	1.7	0.7	1.7	27.4	1.6	12.9	1,020	1,500	1,120
14P	1.5	7	1.7	0.7	1.8	28.6	1.7	12.9	1,020	1,500	1,260
16P	1.5	7	1.7	0.7	1.9	31.0	1.7	12.9	1,020	1,500	1,460
19P	1.5	7	1.7	0.7	1.9	32.4	1.8	12.9	1,020	1,500	1,640
24P	1.5	7	1.7	0.7	2.1	37.1	1.9	12.9	1,020	1,500	2,130
32P	1.5	7	1.7	0.7	2.3	42.5	2.2	12.9	1,020	1,500	2,820
1P	2.5	7	2.2	0.7	1.1	11.0	1.0	8.02	850	1,500	190
2P	2.5	7	2.2	0.7	1.4	17.1	1.1	8.02	850	1,500	410
3P	2.5	7	2.2	0.7	1.4	18.3	1.2	8.02	850	1,500	500
4P	2.5	7	2.2	0.7	1.4	19.5	1.2	8.02	850	1,500	590
5P	2.5	7	2.2	0.7	1.5	22.1	1.3	8.02	850	1,500	740
6P	2.5	7	2.2	0.7	1.6	23.9	1.3	8.02	850	1,500	870
7P	2.5	7	2.2	0.7	1.6	23.9	1.3	8.02	850	1,500	920
8P	2.5	7	2.2	0.7	1.7	25.7	1.4	8.02	850	1,500	1,050
10P	2.5	7	2.2	0.7	1.8	29.1	1.5	8.02	850	1,500	1,330
12P	2.5	7	2.2	0.7	1.8	30.3	1.5	8.02	850	1,500	1,490
14P	2.5	7	2.2	0.7	1.9	31.7	1.6	8.02	850	1,500	1,680
16P	2.5	7	2.2	0.7	2.0	34.3	1.6	8.02	850	1,500	1,940
19P	2.5	7	2.2	0.7	2.1	36.1	1.7	8.02	850	1,500	2,220
24P	2.5	7	2.2	0.7	2.2	41.1	1.8	8.02	850	1,500	2,830
32P	2.5	7	2.2	0.7	2.5	47.3	2.0	8.02	850	1,500	3,800

HV Power Cable

LV Power & Lighting Cable

Instrumentation & Communication Cable

Earthing & Bonding wire

VFD Cable

Technical Information

Instrumentation & Communication Cable

250V BU(c)

No. of Triads	Conductor			Thickness of Insulation	Thickness of sheath	Overall diameter		Conductor Resistance (at 20°C) (Max.)	Insulation Resistance (at 20°C) (Min.)	Test Voltage	Cable Weight Approx.
	Nominal Area	Max. No. of wires	Max. overall dia.			Nominal	Tolerance				
No.	mm ²	EA	mm	mm	mm	mm	±mm	Ω/km	MΩ-km	V/5min.	kg/km
1T	0.75	7	1.2	0.6	1.1	9.2	0.9	26.3	1,170	1,500	130
2T	0.75	7	1.2	0.6	1.2	14.0	1.0	26.3	1,170	1,500	270
3T	0.75	7	1.2	0.6	1.3	15.1	1.1	26.3	1,170	1,500	330
4T	0.75	7	1.2	0.6	1.3	16.5	1.1	26.3	1,170	1,500	400
5T	0.75	7	1.2	0.6	1.4	18.5	1.2	26.3	1,170	1,500	490
6T	0.75	7	1.2	0.6	1.5	21.0	1.2	26.3	1,170	1,500	620
7T	0.75	7	1.2	0.6	1.5	21.0	1.2	26.3	1,170	1,500	640
8T	0.75	7	1.2	0.6	1.6	22.6	1.3	26.3	1,170	1,500	740
10T	0.75	7	1.2	0.6	1.7	25.7	1.4	26.3	1,170	1,500	940
12T	0.75	7	1.2	0.6	1.7	27.1	1.4	26.3	1,170	1,500	1,060
14T	0.75	7	1.2	0.6	1.8	28.5	1.5	26.3	1,170	1,500	1,200
16T	0.75	7	1.2	0.6	1.8	30.2	1.5	26.3	1,170	1,500	1,340
19T	0.75	7	1.2	0.6	1.9	32.7	1.6	26.3	1,170	1,500	1,580
24T	0.75	7	1.2	0.6	2.1	36.5	1.7	26.3	1,170	1,500	1,990
32T	0.75	7	1.2	0.6	2.3	42.1	1.9	26.3	1,170	1,500	2,660
1T	1.0	7	1.4	0.6	1.1	9.7	0.9	19.3	1,050	1,500	150
2T	1.0	7	1.4	0.6	1.3	15.1	1.1	19.3	1,050	1,500	320
3T	1.0	7	1.4	0.6	1.3	16.0	1.1	19.3	1,050	1,500	380
4T	1.0	7	1.4	0.6	1.4	17.8	1.1	19.3	1,050	1,500	470
5T	1.0	7	1.4	0.6	1.5	19.9	1.2	19.3	1,050	1,500	580
6T	1.0	7	1.4	0.6	1.6	22.6	1.3	19.3	1,050	1,500	730
7T	1.0	7	1.4	0.6	1.6	22.6	1.3	19.3	1,050	1,500	760
8T	1.0	7	1.4	0.6	1.6	24.1	1.3	19.3	1,050	1,500	860
10T	1.0	7	1.4	0.6	1.7	27.4	1.4	19.3	1,050	1,500	1,090
12T	1.0	7	1.4	0.6	1.8	29.2	1.5	19.3	1,050	1,500	1,260
14T	1.0	7	1.4	0.6	1.9	30.6	1.5	19.3	1,050	1,500	1,410
16T	1.0	7	1.4	0.6	1.9	32.5	1.6	19.3	1,050	1,500	1,590
19T	1.0	7	1.4	0.6	2.0	35.2	1.7	19.3	1,050	1,500	1,870
24T	1.0	7	1.4	0.6	2.2	39.3	1.8	19.3	1,050	1,500	2,360
32T	1.0	7	1.4	0.6	2.4	45.3	2.0	19.3	1,050	1,500	3,150
1T	1.5	7	1.7	0.7	1.1	10.7	1.0	12.9	1,020	1,500	180
2T	1.5	7	1.7	0.7	1.4	17.2	1.2	12.9	1,020	1,500	410
3T	1.5	7	1.7	0.7	1.4	18.2	1.3	12.9	1,020	1,500	490
4T	1.5	7	1.7	0.7	1.5	20.2	1.3	12.9	1,020	1,500	610
5T	1.5	7	1.7	0.7	1.6	22.6	1.4	12.9	1,020	1,500	760
6T	1.5	7	1.7	0.7	1.7	25.7	1.6	12.9	1,020	1,500	950
7T	1.5	7	1.7	0.7	1.7	25.7	1.6	12.9	1,020	1,500	1,000
8T	1.5	7	1.7	0.7	1.7	27.5	1.6	12.9	1,020	1,500	1,130
10T	1.5	7	1.7	0.7	1.9	31.5	1.8	12.9	1,020	1,500	1,460
12T	1.5	7	1.7	0.7	2.0	33.5	1.8	12.9	1,020	1,500	1,700
14T	1.5	7	1.7	0.7	2.0	34.9	1.9	12.9	1,020	1,500	1,880
16T	1.5	7	1.7	0.7	2.1	37.3	1.9	12.9	1,020	1,500	2,150
19T	1.5	7	1.7	0.7	2.2	40.4	2.0	12.9	1,020	1,500	2,530
24T	1.5	7	1.7	0.7	2.4	45.1	2.3	12.9	1,020	1,500	3,190
32T	1.5	7	1.7	0.7	2.7	52.0	2.6	12.9	1,020	1,500	4,310
1T	2.5	7	2.2	0.7	1.2	11.8	1.1	8.02	850	1,500	240
2T	2.5	7	2.2	0.7	1.4	18.7	1.2	8.02	850	1,500	510
3T	2.5	7	2.2	0.7	1.5	20.1	1.2	8.02	850	1,500	640
4T	2.5	7	2.2	0.7	1.5	22.1	1.3	8.02	850	1,500	790
5T	2.5	7	2.2	0.7	1.6	24.7	1.4	8.02	850	1,500	980
6T	2.5	7	2.2	0.7	1.8	28.2	1.5	8.02	850	1,500	1,240
7T	2.5	7	2.2	0.7	1.8	28.2	1.5	8.02	850	1,500	1,310
8T	2.5	7	2.2	0.7	1.8	30.2	1.5	8.02	850	1,500	1,490
10T	2.5	7	2.2	0.7	2.0	34.6	1.6	8.02	850	1,500	1,920
12T	2.5	7	2.2	0.7	2.1	36.8	1.7	8.02	850	1,500	2,230
14T	2.5	7	2.2	0.7	2.1	38.4	1.8	8.02	850	1,500	2,480
16T	2.5	7	2.2	0.7	2.2	41.0	1.8	8.02	850	1,500	2,840
19T	2.5	7	2.2	0.7	2.4	44.6	1.9	8.02	850	1,500	3,390
24T	2.5	7	2.2	0.7	2.6	49.8	2.1	8.02	850	1,500	4,280
32T	2.5	7	2.2	0.7	2.9	57.6	2.3	8.02	850	1,500	5,770